





| SELF system   |             |          |                   |               |        |
|---|-------------|----------|-------------------|---------------|--------|
| External width: 120mm<br>Internal width: 98mm<br>Length: 1000mm |             |          |                   |               |        |
| Channel reference   | Height (mm) |          | Hydraulic section | Ø outlet (mm) |        |
|   | Total       | Internal | (cm²)             | Vert.         | Horiz. |
| EUROKIT   | 85          | 73       | 66.5              | 110           | -      |

## Review: 2013-03

ULHA Architectural Solutions reserves the right to modify the specifications of any of its products without prior notice.

information about the shown products is only indicative and is based on the existing technical features at the time of leaving.

In the event of any discrepancy in the translation of this document into different languages, the Spenish version will be used.

Latest version in www.ulmeerchitechurel.com

For more details, see technical sheets and installation

## Description

ULMA polymer concrete linear drainage channel model EUROKIT.
Push or click locking system, no bolts.
Load class up to A15. EN 1433 Standard.

Load class up to A15, EN 1435 Standard.

Vertically and horizontally channel aligning tongue and groove joints.

CE Conformity Declaration and compliance with EN 1433 Standard.

External width 120 mm, internal width 98 mm and total length 1000 mm. Total height 85 mm.



ARCHITECTURAL SOLUTIONS



Tel.: +34 943 78 06 00 info@ulmaarchitectural.com ulmaarchitectural.com