



SELF system					
External width: 130mm					
Internal width: 100mm					
Length: 1000mm					
Channel reference	Height (mm)		Hydraulic section (cm ²)	Ø outlet (mm)	
	a	b		Vert.	Horiz.
EUROSELF V+ H95	95	82	66	110	–
EUROSELF V+ H125	125	112	95	110	–
EUROSELF V+ H145	145	132	114	110	–

Review: 2013–12

ULMA Architectural Solutions reserves the right to modify the specifications of any of its products without prior notice.

Information about the shown products is only indicative and is based on the existing technical features at the time of issuing.

In the event of any discrepancy in the translation of this document into different languages, the Spanish version will be used.

Latest version in www.ulmaarchitectural.com

For more details, see technical sheets and installation guide.

Description

ULMA polymer concrete linear drainage channel model EUROSELF V+, self-cleaning optimized V-shaped V+ section.

2 point locking bar system per 1m.

Load class up to C250, EN 1433 Standard.

Vertically and horizontally channel aligning tongue and groove joints.

DoP Declaration of Performance and compliance with EN 1433 Standard.

External width 130 mm, internal width 100 mm and total length 1000 mm. Total external heights available between 95 mm and 145 mm. Installation possible with no slope or stepped fall.

 **ULMA**

ARCHITECTURAL SOLUTIONS

 **DRAINAGE SYSTEMS**

Tel.: +34 943 78 06 00
info@ulmaarchitectural.com
ulmaarchitectural.com