



MINI system					
External width: 120mm					
Internal width: 98mm					
Length: 1000mm					
Channel reference	Height (mm)		Hydraulic section (cm <sup>2</sup> )	Ø outlet (mm)	
	Total	Internal		Vert.	Horiz.
MINIKIT	50	38	34	110	-

Review: 2013-03

ULMA Architectural Solutions reserves the right to modify the specifications of any of its products without prior notice.

Information about the shown products is only indicative and is based on the existing technical features at the time of issuing.

In the event of any discrepancy in the translation of this document into different languages, the Spanish version will be used.

Latest version in [www.ulmaarchitectural.com](http://www.ulmaarchitectural.com)

For more details, see technical sheets and installation guide.

### Description

ULMA polymer concrete linear drainage channel model MINIKIT.

Push or click locking system, no bolts.

Load class up to A15, EN 1433 Standard.

Vertically and horizontally channel aligning tongue and groove joints.

CE Conformity Declaration and compliance with EN 1433 Standard.

External width 120 mm, internal width 98 mm and total length 1000 mm. Total height 50mm.

**ULMA**

ARCHITECTURAL SOLUTIONS

**ULMA**  
DRAINAGE  
SYSTEMS

Tel.: +34 943 78 06 00  
Info@ulmaarchitectural.com  
ulmaarchitectural.com