
# **TECHNICAL DATA SHEET**



Range: Direct dual flush valve with adjustable volumes with brushed chrome-plated front plate

Ref: 14300 - PRESTO 1000 XL E DVA





## > Working pressure :

1 to 5 bar

- > Discharge volume per flush :
  High volume : from 6 to 9 liters adjustable with wrench
  - Low volume : from 2.5 to 5 liters adjustable by the slider on front plate
  - Anti-water-hammering device
  - Automatic 1 l/s flow regulator from 1.2 to 4 bar dynamic working pressure

## > Flow time:

- High volume : 6 to 9 seconds
- Low volume : 2 to 5 seconds

### > Hydraulic supply:

- Right or left square M G 3/4" (20x27)
- Outlet connection on flush pipe Ø 28 mm

### > Material and colour finish:

- Brass body
- Brushed chrome-plated front plate

## > Security:

- Vacuum breaker
- Patented anti-blocking "S" system to avoid the water to flow continuously

## > Delivered with:

- 1 Concealed ABS case
- 1 Brushed chromed -plated front plate
- 1 Stop-valve
- 1 Instruction manual

## > Standards & approvals :

- Acoustic class II
- Brass body in accordance with EN 1982, EN 12164, EN 12165
- Nickel-Chrome plated according to EN12540
- 200-hour neutral salt spray resistant (NSS) in accordance with ISO 9227















